

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1. (Currently amended) A method comprising:
recording a first node local time of receiving a wirelessly transmitted packet at a
first node, the first node local time recorded with a monotonically
increasing clock of the first node;
recording a second node local time of receiving the wirelessly transmitted packet
at a second node, the second node local time recorded with a
monotonically increasing clock of the second node;
wirelessly transmitting the first node recorded local time by the first node to at
least the second node;
receiving the first node recorded local time at the second node and recording the
first node local time of receiving the wirelessly transmitted packet; and
synchronizing a second node timing model with a first node timing model,
wherein the first and second node timing models are updated at
predetermined speeds to provide controlled time ~~intervals~~ interval length
adaptation; and
synchronizing the first and second node timing models with a global clock
associated with the first node and the second node.
2. (Previously presented) The method of claim 1, wherein the wirelessly transmitted
packet comprises a beacon transmitted from a wireless access point.

3. (Previously presented) The method of claim 1, further including:
synchronizing sample numbers of a multimedia stream on the second node with
the second node timing model, the second node timing model having been
synchronized with the first node.
4. (Previously presented) The method of claim 3, wherein the synchronization of
sample numbers in I/O operations is performed by time-stamping IRQs request
with a global time according to the global clock.
5. (Previously presented) The method of claim 1, further including repeating the
method of claim 1 to generate an updated second node timing model to
synchronize with the first node timing model.
6. (Cancelled)
7. (Currently amended) The method of claim 1, further ~~includes~~ including:
recording a third node local time of receiving the wirelessly transmitted packet
from the first node at a third node and recording the first node local time
of receiving the wirelessly transmitted packet; and
synchronizing a third node timing model with the first node timing model and the
second node timing model, and further synchronizing the first, second and
third node timing models with the global clock associated with the first
node, the second node, and the third node.

8. (Currently amended) A machine-readable medium having stored thereon sets of instructions which when executed by a machine cause the machine to:
- record a first node local time of receiving a wirelessly transmitted packet at a first node, the first node local time recorded with a monotonically increasing clock of the first node;
- record a second node local time of receiving the wirelessly transmitted packet at the second node, the second node local time recorded with a monotonically increasing clock of the second node;
- wirelessly transmit the first node recorded local time by the first node to at least a second node;
- receive the first node recorded local time at the second node and record the first node local time of receiving the wirelessly transmitted packet; and
- synchronize a second node timing model with a first node timing model, wherein the first and second node timing models are updated at predetermined speeds to provide controlled time ~~intervals~~ interval length adaptation; and
- synchronize the first and second node timing models with a global clock associated with the first node and the second node.
9. (Previously presented) The machine-readable medium of claim 8, wherein the wirelessly transmitted packet comprises a beacon transmitted from a wireless access point.
10. (Previously presented) The machine-readable medium of claim 8, wherein the sets of instructions when executed further cause the machine to:

synchronize sample numbers of a multimedia stream on the second node with the second node timing model, the second node timing model having been synchronized with the first node.

11. (Previously presented) The machine-readable medium of claim 10, wherein the synchronization of sample numbers in I/O operations is performed by time-stamping IRQs request with a global time according to the global clock.

12-13. (Cancelled)

14. (Previously presented) The machine-readable medium of claim 8, wherein the sets of instructions when executed further cause the machine to:
record a third node local time of receiving the wirelessly transmitted packet from the first node at a third node and recording the first node local time of receiving the wirelessly transmitted packet; and
synchronize a third node timing model with the first node timing model and the second node timing model, and further synchronize the first, second and third node timing models with the global clock associated with the first node, the second node, and the third node.

15. (Currently amended) A system comprising:
a first node to record a first node local time of receiving a wirelessly transmitted packet, the first node local time recorded with a monotonically increasing clock of the first node;
a second node to record a second node local time of receiving the wirelessly transmitted packet at the second node, the second node local time recorded with a monotonically increasing clock of the second node;

the first node to wirelessly transmit the first node recorded local time to at least the second node;

the second to receive the first node recorded local time and record the first node local time of receiving the wirelessly transmitted packet; and

the second node to synchronize a second node timing model with a first node timing model, wherein the first and second node timing models are updated at predetermined speeds to provide controlled time ~~intervals~~ interval length adaptation, and synchronize the first and second node timing models with a global clock associated with the first node and the second node.

16. (Previously presented) The system of claim 15, wherein the wirelessly transmitted packet comprises a beacon transmitted from a wireless access point.
17. (Currently amended) The system of claim 15, wherein the second node is further to:

synchronize sample numbers of a multimedia stream on the second node with the second node timing model, the [[the]] second node timing model having been synchronized with the first node.
18. (Previously presented) The system of claim 17, wherein the synchronization of sample numbers in I/O operations is performed by time-stamping IRQs request with a global time according to the global clock.
- 19-20. (Cancelled)

21. (Currently amended) The system of claim 15, further ~~includes~~ including:
- a third node to record a third node local time of receiving the wirelessly transmitted packet from the first node and record the first node local time of receiving the wirelessly transmitted packet; and
- the third node to synchronize a third node timing model with the first node timing model and the second node timing model, and further to synchronize the first, second, and third node timing models with the global clock associated with the first node, the second node, and the third node.